

Product Specification

GX-POE29-RX548

Date: 2020/08/21

Chipset		IP1717B
Standard		IEEE802.3、IEEE802.3u、IEEE802.3x、IEEE802.2af、IEEE802.3at
Layer 2 Switching		Backplane Bandwidth: 1Gbps
		Packet Forwarding Speed: 12.96Mbps
		All Ports Speed Forwarding
Port		4*10/100M Ethernet Port (PoE) +1 * 10/100M UPLINK port
Power	Voltage	4* PoE port with 802.3at/af standard
	Input Voltage	DC48-57V
Power Consumption		2W (standby situation)
Maximum Output Power		13.5W (single port)
The Size of the MAC Address Table		4K
Features		IEEE 802.3x traffic control under Full-Duplex mode
		Storm control based on the data transmission speed of the port
		PPS-based storm control
VLAN		Turn on the VLAN button in the panel, 4 PoE ports will be isolated from each other but available to communicate with the UPLINK port. When VLAN is off, 5 ports can communicate with each other.
Operating Condition	Operating Temperature	-20~60°C
	Storage Temperature	-50~80°C
	Humidity	≤10~90% (non-condensed)

Product Size & Weight:

300*220*30MM

1kg

**Package List:**

1 * GX-POE29-RX548

1 * Ring

1 * Manual

**Package Size & Weight:**

429X268X94MM

1.2kg

Package Size & Weight:

430*295*245MM

12kg

QTY: 10PCS



Label

Label Size: 70 * 40MM

Label Material: silver sticker

Label Surface: silver background and black words

