SPEC SHEET



HD HYBRID DOME CAMERA

4MP IR Dome Camera Supports TVI, CVI, AHD, 960H Applications



The GX-SMT-XHD744F-28 is a 4MP (2560x1440) dome camera constructed with a 2.8mm lens. This 4 MP Camera is IP67 rated and provides HD Image quality and is ideal for numerous indoor/outdoor applications such as commercial applications, home or office use as well as monitoring hallways, unattended storage areas and various other installation applications.

- · IR up to 20M (66 ft)
- · 2560 X 1440 Picture Quality
- · 2IR LEDs
- · 3-axis Gimbal
- · AHD+TVI + CVI + 960H Output
- · Ture Day Night
- · OSD Menu
- · IP 67/IK 10
- 12V DC
- · 3 Year Warranty

PART #: GX-SMT-XHD744F-28

LENGTH: 5.2"

HEIGHT: 4.3"

WEIGHT: 1.1 Lbs.

Specifications

Model	GX-SMT-XHD744F-28
Image Sensor	1/2.7" Progressive Scan CMOS
Signal System	PAL/NTSC
Min. illumination	Color:0.05Lux@(F1.2,AGC ON);
	B/W:0Lux@(IR LED ON)
S/N Ratio	≥50dB
Day & Night	ICR
Shutter Speed	PAL:1/25-1/50000, NTSC:1/30-1/10000
Wide Dynamic Range	dWDR
Digital Noise Reduction	2D
Lens	2.8mm
FOV	90°
IR LED	2pcs
IR Wavelength	850nm
IR Range	20m
OSD Joystick	Support
Up the Coax	Support
IMAGE	
Effective Resolution	2560x1440
Frame	PAL:25fps ,NTSC:30fps
VIDEO OUTPUT	
Max Distance	75-5, 300m
Video Output	AHD/TVI/CVI/CVBS
GENERAL	
Power Supply	DC12V±10%
Power Consumption	3.5W(Max)
Operating Temperature	-10 °C ~ 55 °C (14°F ~ 131 °F)
Operating Humidity	0% - 85% RH
Ingress Protection	IP67/IK10
Material	Aluminium Alloy
Product Dimensions	Ф110*85mm
Product Weight	390g