

AC328-FD4

8 MP Outdoor Turret Camera

TurboHD[™]



- **8 MP High Performance CMOS**
- **Up to 3840 x 2160 Resolution**
- **2.8 mm and 6 mm Fixed Lens Options**
- **3D DNR, DWDR**
- **EXIR.0 up to 195 ft (60 m) IR Range** Conditions.
- **Multiprotocol Output:**
TVI/AHD/CVI/CVBS
- **Up-the-Coax (HIKVISION-C)**
- **IP67 Protection**

Available models:
AC328-FD4-2.8



Specifications

AC328-FD4-2.8	
Camera	
Image Sensor	8.29 MP progressive scan CMOS
Frame Rate	TVI: 8 MP @ 12.5 fps, 8 MP @ 15 fps, 5 MP @ 20 fps, 4 MP @ 25 fps, 4 MP @ 30 fps, 2 MP @ 25 fps, 2 MP @ 30 fps
CVI	8 MP @ 12.5 fps, 8 MP @ 15 fps
AHD	8 MP @ 12.5 fps, 8 MP @ 15 fps
CVBS	960H NTSC
Resolution	3840 (H) x 2160 (V)
Minimum Illumination	Color: 0.01 lux @ (f/1.2, AGC on), 0 lux with IR
Shutter Speed	1/15 s to 1/50,000 s
Lens	2.8 mm and 6 mm fixed lens options
Horizontal Field of View	42.2° (2.8 mm), 50.8° (6 mm)
Lens Mount	M16
Day/Night	IR cut filter
Angle Adjustment	Pan: 0° to 360°; tilt: 0° to 180°; rotate: 0° to 360°
Synchronization	Internal synchronization
DWDR	105 dB
Menu	
AGC	Yes
Day/Night Mode	Auto/color/BW (black and white)
White Balance	Auto/manual
BLC	Yes
Language	English
Functions	Brightness, sharpness, DNR, mirror, Smart IR, HLC
Interface	
TVI Video Output	1 HD analog output
Switch Button	TVI/AHD/CVI/CVBS
General	
Operating Conditions	40° F to 140° F (-40° C to 60° C), humidity: 90% or less (non-condensation)
Power Supply	12 VDC ± 25% (only one power supply can be used per camera)
Power Consumption	Maximum 5.3 W
Protection Level	IP67
Material	Enclosure: plastic, main body: metal
IR Range	Up to 195 ft (60 m)
Communication	Up-the-Coax, protocol: HIKVISION-C (TVI output)
Dimensions	Ø 4.32" x 3.6" (Ø 109.82 mm x 91.03 mm)
Weight	Approximately 0.71 lbs (320 g)

Accessories (not included)

				
WMS + PC110T Wall Mount Short and 130 mm Pendant Cap for Turret Cameras	PM Pole Mount	CM Corner Mount	ABS Angled Base	CBS Conduit Base

Dimensions

