

NV-PIR500

Galaxy NV 5MP UHD IR Mini Hidden IP Camera



FEATURES

- 1/3" CMOS sensor
- Max. 5MP resolution 2592 x 1944 output
- low illumination 0.01Lux
- MP HD resolution 2592 x 1944 realtime output
- Ultra low illumination 0.01Lux
- Day/Night (ICR), AWB, 2D/3D-DNR, IR-CUT
- D-WDR, Motion Detection, Human Detection, Privacy Mask, Mirror
- RTSP and Onvif 17.06 compatible
- H.265/H.264 dual-stream media server
- Easy-to-use P2P Cloud service
- Multi web browser, PC Client, mobile APP remote access
- RJ45 100Mbps network port, IEEE802.3af PoE
- Lightning protection 4000V
- Plastic housing, IP65
- 12x Dia. 5 IR Leds, IR distance 10-15 meters
- HD 3.7mm MP Pinhole lens

SPECIFICATIONS

Model	NV-PIR500
Camera	
Image Sensor	1/3" CMOS
Effective Pixels	5 Megapixels
Electronic Shutter	AUTO
Min. Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on
Day/Night	Auto/Color(B/W)/Timing
WDR	Digital WDR
White Balance	Auto/Manual
AGC/BLC/HLC	Support
DNR	2D/3D DNR
Other	Multi-lanes OSD, Motion Detection, Privacy Mask, Mirror
Encode	
Video Standard	H.264/H.265
Video Resolution	Main Stream: 30fps@5MP(2592x1944)/4MP/3MP/1080P/720P; Sub stream: 30fps@D1/VGA/360P/CIF, etc.
Video Bitrates	512Kbps - 8Mbps, VBR/CBR
Audio Standard	G.711-u/G.711-a/AAC
Built-in Mic	Optional
Smart Event	Human Detection, Motion Detection
IR Led	
IR Led	12x Dia.5 IR Leds
IR Distance	10-15 M
Lens	
Focal length	3.7mm MP Pinhole lens
Optional Function	
Optional	POE, Audio, etc.
Network Services	
Protocol	HTTP/RTSP/FTP/NFS/SNMP/DHCP/NTP, etc.
P2P	Yes
Web	IE , Firefox 32bit ESR, etc.
Media	CMS, Android, IOS
ONVIF	17.06 compatible
General	
Network Port	1-RJ45, 100Mbps, POE optional
Power Supply	12 VDC ± 10%
Power Consumption	< 5 W
Operating Temp.	-30°C (-60)°C, 10%-90%RH