

Features

- IEEE 802.3af compliant
- Delivers power up to 100 meters
- Auto-determine the necessary power requirements
- Plug-and-Play, requires no configuration
- External power adapter supply



Specification

HARDWARE FEATURES	
Interface	1 10/100 RJ45 Port AUTO Negotiation/AUTO MDI/MDIX
Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) EIA/TIA-568 100ohm STP (maximum 100m) 100BASE-TX: UTP category 5, 5e cable (maximum 100m) EIA/TIA-568 100ohm STP (maximum 100m)
LED Indicator	PWR
Dimensions (W x D x H)	3.2x2.0x0.9 in.(81x52x24 mm)
Power Supply	15.4W (Max. 48VDC)
SOFTWARE FEATURES	
Basic Function	Compatible With IEEE 802.3af Compliant PDs Delivers Power Up To 100 Meters Auto-Determine The Necessary Power Requirements
OTHERS	
Certification	FCC, CE
Environment	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing

Specifications & Features: