

Caractéristiques

High Speed Fingerprint Matching

- VF30 Pro offers a massive memory capacity to manage largest number of users. A single unit of VF30 Pro can accommodate up to 3,000 users, 3,000 cards and 100,000 logs.

Versatile Interfaces

- VF30 Pro comes with not only a TCP/IP interface, but also more traditional interfaces (RS-485, Wiegand) to provide higher flexibility and multiple installation options for different environments. It also offers 2 internal inputs and 1 internal relay output to control peripheral devices.

Freedom Infinite

- VF30 Pro supports WiFi mode by optional, to provide users with lower installation cost, simpler configuration and lower maintenance cost.



Spécification

Capacity	
Fingerprint Capacity	3,000
Card Capacity	3,000
Log Capacity	100,000
Interface	
Comm	TCP/IP, RS485, POE (Standard IEEE802.3af), Optional WiFi
Relay	Relay Output (COM, NO, NC)
I/O	Door Sensor, Exit Button, Door Bell, Wiegand in/out, Anti-pass Back

Capacity

Interface

Feature	
Identification Mode	Finger, Password, Card
Identification Speed	<0.5s
Card Reading Distance	1~5cm (125KHz), 13.56MHz <2CM) for Standard CR80 Card
Image Display	Support

Capacity
Feature
Interface

Time Attendance Mode	8
Group, Time Zone	16 Group, 32 Time Zone
Work Code	6 Digit
Short Message	50
WebServer	Support
Daylight Saving	Support
Voice Prompt	Support
Clock Bell	30 Groups
Software	Anviz CrossChex
	Hardware
CPU	1GHz Quick CPU
Sensor	Touch Active Sensor
Scanning Area	22*18mm
RFID Card	Standard EM, Optional Mifare

Capacity

Feature	
Hardware	
Interface	
Display	2.4" TFT LCD
Dimensions(W * H * D)	80 * 180 * 40mm
Working Temperature	-30~ 60
Humidity	20% to 90%
PoE	Standard IEEE802.3af
Power	DC12V 1A
IP Grade	IP55