

EZVIZ C6N Smart Wi-Fi Pan & Tilt Camera

Features

The C6N from EZVIZ comes equipped with a Smart IR function, which uses advanced infrared (IR) lighting to capture more details in dim light. With its 360-degree field of view and smart tracking function, you won't need to worry about missing a thing.

- 1080p
- Smart Night Vision with Smart IR (up to 10m / 33ft.)
- Motorized Pan and Tilt 360deg. Visual Coverage
- Sleep Mode for Privacy Protection
- Motion Detection
- Smart Tracking
- Two-way Talk
- View from Anywhere
- Wi-Fi 2.4 GHz
- MicroSD Slot (up to 256 GB)

Go to official website >>>



Specification

Camera	
Image Sensor	1/4" Progressive Scan CMOS
Shutter Speed	Self-adaptive shutter
Lens	4mm@ F2.4, view angle: 85deg. diagonal, 75deg. horizontal, 45deg. vertical
Lens Mount	M12
Day & Night	IR-cut filter with auto-switching
DNR	3D DNR
WDR	Digital WDR
Compression	
Video Compression	H.264
Video Bit Rate	Full HD, HD, Standard. Adaptive bit rate.

Image

Image		
Max. Resolution	1920 x 1080	
Frame Rate	Max. 15fps; Self-adaptive during network transmission	
Network		
Smart Alarm	Motion detection	
Wi-Fi Pairing	AP Pairing	
Protocol	EZVIZ Cloud Proprietary Protocol	
Interface Protocol	EZVIZ Cloud Proprietary Protocol	
Interface		
Storage	MicroSD card slot (Max. 256 GB)	
Power	Micro USB	
Wired Network	RJ45 X 1 (10M/100M self-adaptive Ethernet port)	
Wi-Fi		
Standard	IEEE802.11 b/g/n	
Frequency Range	2.4 GHz ~ 2.4835 GHz	
Channel Bandwidth	Supports 20MHz	
Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK	
Transmission Rate	11b: 11 Mbps, 11g: 54 Mbps, 11n: 72 Mbps	
General		
Power Supply	DC 5V/1A	
Power Consumption	5W max	
IR Range	MAX. 10m (32.81 fts)	
Dimensions	88 mm x 88.2 mm x 119 mm (3.46" x 3.47" x 4.69")	
Packaging Dimensions	103 mm x 103 mm x 168 mm (4.06" x 4.06" x 6.61")	
Bare Weight	218g (0.48lb)	
Packaging Contents		
Packaging Contents	C6N camera; Base; Screw Kit; Power Cable 3m (9.8 ft.); Drill Template; Power Adapter; Quick Start Guide	
Operating Environment		
Temperature	-10deg. C to 45deg. C (14deg. F to 113deg. F)	
Humidity	95% or less (non-condensing)	
Certifications		
Certifications	FCC / UL / CE / WEEE / REACH / RoHS	