

Features

The C8C is EZVIZ's first outdoor WiFi Pan/Tilt Camera, a giant breakthrough combining an exquisite design with comprehensive functionality. Capturing more details than ordinary outdoor cameras do, this camera ensures reliable, all-around outdoor protection.

- 1080p
- Motorized Pan & Tilt for 360deg. Visual Coverage
- AI-Powered Person Detection
- Color Night Vision
- Active Defense
- IP65 Dust and Water Protection
- Audio Pick-up
- Supports 2.4 GHz WiFi
- H.265 Video Technology
- Supports MicroSD Card Storage (up to 256 GB)
- EZVIZ CloudPlay Storage



[Go to official website >>>](#)

Specification

Specifications	
Model	CS-C8C (1080P)
Camera	
Image Sensor	1/2.7" Progressive Scan CMOS
Shutter Speed	Self-adaptive shutter
Lens	4mm @ F1.6, view angle: 87deg. (Horizontal), 105deg. (Diagonal) 6mm @ F1.6, view angle: 55deg. (Horizontal), 66deg. (Diagonal)
PT Angle	Pan: 352deg., Tilt: 95deg.
Minimum Illumination	0.5 Lux @(F1.6, AGC ON), 0 Lux with IR
Lens Mount	M12

Day & Night	IR-cut filter with auto-switching
DNR	3D DNR
WDR	Digital WDR
BLC	Supports
Black & White Night	30 m / 100 ft.
Video & Audio	
Max. Resolution	1920 x 1080
Frame Rate	Max:30 fps; Self-Adaptive during network transmission
Video Compression	H.265 / H.264
Video Bit Rate	Full HD; Hi-Def; Standard. Adaptive bit rate.
Audio Bit Rate	Self-Adaptive
Max. Bitrate	2 Mbps
Network	
Wi-Fi Standard	IEEE802.11b, 802.11g, 802.11n
Frequency Range	2.4 GHz ~ 2.4835 GHz
Channel Bandwidth	Supports 20 MHz
Security	64 / 128-bit WEP, WPA / WPA2, WPA-PSK / WPA2-PSK
Transmission Rate	11b: 11Mbps, 11g : 54Mbps, 11n: 72Mbps
Wi-Fi Pairing	AP pairing
Protocol	EZVIZ cloud proprietary protocol
Interface Protocol	EZVIZ cloud proprietary protocol
Wired Network	RJ45 x 1 (10 M / 100 M Adaptive Ethernet Port)
Storage	
Local Storage	MicroSD card slot (Max. 256G)
Cloud Storage	EZVIZ Cloud Storage
Function	
Smart Alarm	AI Person Detection
Customized Alert Area	Supports
Audio	Supports mic
General Function	Anti-Flicker, Dual-Stream, Heart Beat, Password Protection, Watermark
General	
Operating Conditions	-30deg.C ~ 60deg.C (14deg.F to 113 deg.F), Humidity 95% or less (non-condensing)
IP Grade	IP65
Power Supply	DC 12V / 1A
Power Consumption	MAX. 6W
Dimensions	158 x 157 x 149 mm (6.22 x 6.18 x 5.87 inch)

Packaging Dimensions	197 x 185 x 205 mm (7.76 x 7.28 x 8.07 inch)
Weight	885 g (31.22 oz)
Net Weight	510 g (17.99 oz)
In the box:	
In the box:	C8C Camera 1.5-Meter Power Adapter Screw Kit Waterproof Kit Drill Template Regulatory Information Quick Start Guide
Certifications:	
Certifications:	UL / FCC / CE / WEEE / REACH/ ROHS