

Features

- IP video intercom kit for villa or house, only one call button
- DS-KD8003-IME1/Surface x1
- DS-KH6320-WTE1 x1
- 4 port standard PoE switch x1
- 16GB TF card x1
- European power supply adaptor included (please mark for other standards when you order)



Specification

System Parameters

Processor Embedded MCU Processor

Operation System Embedded Linux Operation System

Display Parameters

Display Resolution 1024 × 600

Display Screen 7-inch colorful TFT screen

Audio Parameters

Audio Compression Rate 64 Kbps

Audio Compression Standard G.711 U

Audio Input Built-in omnidirectional microphone

Audio OutputBuilt-in loudspeaker

Audio QualityNoise suppression and echo cancellation

Network Parameters

Ethernet10/100 Mbps Self-Adaptive Ethernet

Network ProtocolTCP/IP, RTSP

Device Interfaces

I/O Input4

I/O Output2

General

Power Supply12 VDC/PoE (IEEE 802.3af)

Power Consumption<=10 W

Working Temperature-40° C to +60° C (-40° F to 140° F)

Working Humidity10% to 95%

Dimension (L X W X D)200 mm × 140 mm × 15.1 mm (7.9" × 5.5" × 0.6")

Weight

683 g (with packaging)

355 g (without packaging)

Ip Protection LevelIP65

Memory128 MB

Dimensions(L × W × H)98 mm × 99.8 mm × 43.9 mm (3.86" × 3.93" × 1.73")
