

Features

- Designed for surveillance, high reliability and stability.
- 42.5" LED backlight with wide display equipment.
- 4K resolution is 4 times the resolution of 1080p, providing a wider view and finer details.
- Multiple inputs: HDMI, VGA, USB.
- Narrow front bezel.
- Wide view angle: horizontal 178°, vertical 178°.
- 24/7 operation.



Specification

Display

Screen Size42.5"

Active Display Area 941.184 (H) mm \times 529.416 (V) mm

Resolution3840 × 2160

BacklightD-LED

Pixel Pitch0.2451 (H) mm \times 0.2451 (W) mm

Brightness400 cd/m²

Viewing Angle178° (H)/178° (V)

Color Depth1.07 billion

Contrast Ratio4000:1

Response Time8 ms

Interface

Video & Audio InputHDMI \times 2, VGA \times 1, AUDIO IN \times 1

Video & Audio OutputAUDIO OUT × 1

Data Transmission InterfaceUSB 2.0 \times 1, USB 3.0 \times 1

Control InterfaceRS-232 × 1

Loudspeaker8 W \times 2

Power

Power Supply100 to 240 VAC, 50/60 Hz

Power Consumption</= 120 W

Standby Consumption 0.5 W

Working Environment

Working Temperature5°C to 40 °C (41 °F to 104 °F)

Working Humidity20% to 80% RH (non-condensing)

Storage Temperature-20 to 60 (-4 to 140)

Storage Humidity10% to 90% RH (non-condensing)

General

Vesa200 mm \times 200 mm/400 mm \times 400 mm

Product Dimensions (W \times H \times D)968.2 (W) mm \times 559.4 (H) mm \times 60.9 (D) mm (38.12" \times

 $22.02" \times 2.40"$

Mounting TypeWall mounting

Package Dimensions (W \times H \times D)1070 (W) mm \times 696 (H) mm \times 159 (D) mm (42.13" \times

 $27.40" \times 6.26"$

Net Weight8.6 kg (18.96 lb.)

Gross Weight11.7 kg (3.75 lb.)

Packing ListPower cable \times 1, HDMI cable \times 1, remote control \times 1, user manual \times 1

RemarksIf the appearance and parameters in this specification vary from the actual product, the later prevails. You can also consult local sale staff.

ColorBlack