



Caractéristiques

Trailer: Tubular steel welded construction, four 2,000 lb. stabilizer corner jacks for added wind stability, front access fork lift pockets, crane lifting eyes, round full wheel fenders that are bolted to the trailer frame, axle assembly 3,500 lb., double-eye leaf springs, 15" wheels / tires, red and white conspicuity tape

Drawbar: Tilting, 2" ball hitch, swivel wheel tongue jack, flat-four trailer lights plug

Tower: 24-foot telescoping tower rotating 355 degrees, hand-operated winch for raising and lowering tower

Camera mount: Multi-head camera box: 4x pendant arms (1-1/2" NPT), 5X Cat5E cable, 1X 16/2 power

Solar: High-efficiency photovoltaic solar modules, electric actuator-tilt solar panel array, solar panel capacity 800W, Smart MPPT blue-tooth solar controller, battery "time-remaining" feature, communication module

Control Box: Aluminum control box with 3-point locking door (24"W x 25"H x 10"D), solar / battery power management meter, master battery/solar disconnect switch, power inverter 375W, Solar panel tilt switch, battery protect, Cerbo GX communications mode

Batteries: Single Wanco battery box with bolted Lid, four 12V sealed AGM Batteries (400 Ah @

24Vdc Total Capacity), 50 Amp battery charger, (optional second battery box available – 800Ah capacity)

Standard color: Powder coated flat black frame and mast, white battery box and NEMA box

* Please note that shipping costs for this product will be quoted separately.